

Bestaande maaiveld
DHM Vlaanderen

Schalen: Lengte: 1/500
Hoogte: 1/100

Persleiding Ø700 / Ø900
VERGELIJKINGSVLAK
-5.00m T.A.W.

Rode Wiel
B1 Intersectiepunt
Slopede
1.20
1.50
1.69
2.50

10°

Persleiding Ø700 / Ø900
VERGELIJKINGSVLAK
-5.00m T.A.W.

Profielnummer																																																																																																										
Samengestelde afstand																																																																																																										
Bestaand maaiveld		5,79	400,00	5,84	410,00	5,90	420,00	5,90	430,00	5,85	440,00	5,81	450,00	5,82	460,00	5,83	470,00	5,83	480,00	5,79	490,00	5,76	500,00	5,77	510,00	5,74	520,00	5,65	530,00	5,84	540,00	5,69	550,00	5,63	560,00	5,77	570,00	5,81	580,00	5,78	590,00	5,77	600,00	5,76	610,00	5,73	620,00	5,84	630,00	5,82	640,00	5,56	650,00	5,31	660,00	5,07	670,00	5,96	680,00	5,56	690,00	5,35	700,00	5,42	710,00	5,41	720,00	5,19	730,00	5,10	740,00	5,26	750,00	760,00																																
Toekomstig maaiveld																																																																																																										
DWA	Putnr. en tussenafstand	deel 5 - 430m deel 5 - 430m deel 5 - 430m IP3 deel 4 - 402m																																																																																																								
	Helling en Ø	Persleiding Ø900 - 2% Persleiding Ø900 - 2% Persleiding Ø900 - 2% Persleiding Ø700 - gestuurde boring																																																																																																								
	Bodemhoogte	1,94																										2,14																										2,34																										2,53																										2,59
	Max. hydraul. peil																																																																																																									
	Legkarakteristieken																																																																																																									

